



## 22815-B / 22815DT

- Even fading pattern without hotspots
- **Twice wider** illumination span than model 22807-B through superior optical design
- Water tight configuration to withstand the severe applications
- Low power consumption
- Available with Built-in Deutsch connector

<b>Voltage</b>	12~36V
<b>Beam pattern</b>	Flood
<b>SMD high power LEDs</b>	9
<b>Watt</b>	22
<b>Raw Lumen</b>	2160
<b>Effective Lumen</b>	1427
<b>HV CD</b>	5280
<b>Current Draw</b>	13.5V at 1.5A±0.25A 28V at 0.73A±0.12A
<b>Connection(22815-B)</b>	280mm cable
<b>Connection(22815DT)</b>	built-in Deutsch connector
<b>Weight</b>	685g
<b>IP Rating</b>	IP69K
<b>Std Pack Qty</b>	20

<b>Material</b>	
<b>lens</b>	PC
<b>housing</b>	aluminum
<b>bracket</b>	stainless steel
<b>hardware</b>	stainless steel

<b>Resistant</b>	
<b>water</b>	✓
<b>dust</b>	✓
<b>shock</b>	✓
<b>warpage</b>	✓
<b>temperature</b>	-30°C ~ 50°C



# LED WORK LAMP



built-in Deutsch connector

